

July 2017  
Volume 33 Number 07

www.landscapeonline.com

# LANDSCAPE ARCHITECT

AND SPECIFIER NEWS

THE INDUSTRY TRADE MAGAZINE FOR COMMERCIAL LANDSCAPE SPECIFIERS NATIONWIDE!

**Find 66 World Premieres  
in this Issue**

World Premieres

For Details See Page 6



two water features within the new Nature Garden at the Natural History Museum of Los Angeles. This 3.5-acre site represents the natural streams, lakes and the concrete channel urban rivers and drainage corridors of L.A. County. The museum is just north of the L.A. Memorial Coliseum. Exposition Park and the California Science Center are adjacent to the museum on the east side.

Above: At the Natural History Museum Nature Garden in Los Angeles a two-and-a-half-foot waterfall cascades over a stone ledge into the 54,000-gallon pond. The grotto-like setting offers some protection for the turtle inhabitants from predators and the heat. The pond is from 18 inches deep to 4.5 feet deep. An in-pond biological filter and nutrient removal mechanical filter maintain clear water. A UV disinfection system is used in lieu of chemical treatments because of the turtles and minnow-like Arroyo chubs.

#### Natural History Museum Nature Garden

PACE Advanced Water Engineering provided engineering design services as part of the Mia Lehrer+Associates team for

The 4,500-sq. ft. pond and stone block shoreline create a natural appearance. Flat boulders and a two-and-a-half-foot waterfall form a grotto. The pond holds 54,000 gallons and has a depth from 18 inches up to 4.5 feet. A UV system sanitizes biological nutrients and maintains clear water, obviating the chemical treatments that would otherwise harm the turtle inhabitants.

The pond transitions to a formal concrete canal feature connected by a dry gulch, simulating the L.A. River. The canal leads

to a 175-square foot fountain play area with polished granite jetties for seating. The water originates from a trough at the top of the slab and flows a quarter inch deep over a flat LithoCrete surface.

Below: The pond transitions to a 175-sq. ft. wet pad area with three polished granite jetties. Children and adults can cool their feet in the quarter-inch deep water. About 4,000 gallons of water flow over the architectural concrete surface. Controllers automatically deliver the appropriate levels of pool chemicals, a UV system disinfects the water and sand filtration keeps the water clean.



**HARDSCAPE DESIGNS  
CRAFTED BY BORGERT**

**BORGERT**  
PAVERS | SLABS | WALLS | EST. 1923

Your reputation is everything. It generates repeat business and separates you from your competition. That's why you need products you're proud to attach your name to. For more than 90 years, we've delivered the features you need - Unmatched durability. Premium quality. Limitless designs and colors. That's why these in the industry choose Borgert.

*Crafting your vision.*

Request a Lunch and Learn or for more information call 800.622.4952 | [borgertproducts.com](http://borgertproducts.com)

Information Request # 505

Hydraway is the industry's

# FASTEST Drainage System

with a leading

# 70% In-flow Rate

“For several years, we have specified Hydraway products as part of the subsurface drainage design under natural and synthetic athletic fields, utilizing both horizontal and vertical applications. We could not be more pleased with the high quality and performance of the products.”

Ed Norton, Landscape Architect, Holsinger Norton Partners, Inc.

866.808.0991 | [hydraway.net](http://hydraway.net)

The Ultimate Solution for Natural Grass Fields, Synthetic Turf, & Golf Courses Drainage

Information Request # 516

## KILLER SEAM ADHESIVE

NEW NORDOT® ADHESIVE #34R-4(Super)

KILLS HOT MELT ADHESIVES! Less labor cost, fewer call-backs, less equipment = BIG \$\$ Savings! Installs faster in hot or cold weather (just open the pail and use).

Also, makes an outstanding repair and total glue-down adhesive because a properly set seam stays put during installation.

---

WANT THE FACTS? - Write, Call or Visit our Website:

P.O. Box 241  
Scotch Plains, NJ 07076 U.S.A.  
Tel: (908) 233-6803  
Fax: (908) 233-6844  
E-mail: [info@nordot.com](mailto:info@nordot.com)  
Web: [www.nordot.com](http://www.nordot.com)

- Doesn't curl, slip, creep open, etc. even when windy.
- Excellent fresh and salt water resistance when submerged.
- Withstands sudden and unexpected rain during installation before it sets.
- Expect years of outstanding long-term exterior durability.

NORDOT® Adhesive #34R-4(Super) is a one-part, thixotropic, high green strength, low odor, solvent-based curing urethane that can be used for installations at any temperature the installer can work from below freezing to intense desert heat. Just open the pail and use. Meets SCAQMD Rule 1168 for outdoor use.

Information Request # 580